

Router Inalámbrico UAP-AC-LITE

- Dimensions 160 x 160 x 31.45 mm (6.30 x 6.30 x 1.24")
- Weight With Mounting Kits 170 g (6.0 oz) 185 g (6.5 oz)
- Networking Interface (1) 10/100/1000 Ethernet Port
- Buttons Reset
- Power Method 802.3af/A PoE 24V Passive PoE (Pairs 4, 5+; 7, 8 Return)
- Power Supply 24V, 0.5A Gigabit PoE Adapter*
- Power Save Supported
- Maximum Power Consumption 6.5W
- Maximum TX Power
 - 2.4 GHz 20dBm
 - 5 GHz 20dBm
- Antennas (2) Dual-Band Antennas, 3 dBi Each
- Wi-Fi Standards 802.11 a/b/g/n/r/k/v/ac
- Wireless Security WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
- BSSID Up to 8 per Radio
- Mounting Wall/Ceiling (Kits Included)
- Operating Temperature -10 to 70° C (14 to 158° F)
- Operating Humidity 5 to 95% Noncondensing
- Certifications CE, FCC, IC

- Advanced Traffic Management VLAN 802.1Q
- Advanced QoS Per-User Rate Limiting
- Guest Traffic Isolation Supported
- WMM Voice, Video, Best Effort, and Background
- Concurrent Clients 250+